



OK100

键盘加密控制器

规格书

Version 1.0

October 12, 2010

oTHE Technology Inc.

©Copyright oTHE Technology Inc. 2010

Update History		
Version	Date	Description
1.0	October 12, 2010	Preliminary version

Chapter	Contents	Page
1.	简介.....	4
2.	功能.....	4
3.	脚位圖.....	4
4.	脚位定义.....	4
5.	内部方块图.....	5
6.	封装(SOIC-16Pin).....	5
7.	电气特性.....	6
	7-1 最大极限.....	6
	7-2 DC 特性.....	6
	7-3 AC 特性.....	7
8.	应用电路.....	10

1. 简介

OK100 是一键盘加密控制器。内含 8-Bit MCU、加密运算器、8K Bytes Flash、SRAM、USB 1.1 控制器、PS2 控制器等电路。透过 OK100 与软件端的加密整合技术，可以主动防治网络黑客或键盘侧录软件等的恶意盗取个人信息。OK100 是一 SOIC-16Pin 的封装，可内建在 PC 键盘内、做成 USB/PS2 Adapter，或是内建在主板内，解决使用者在上网时的疑虑，及被侧录的情况发生，是一个同时可以做到低成本、高安全性与实用性的加密保护方案。

2. 功能

- ◆ 内建 8-Bit MCU 及加密运算器
- ◆ USB 2.0 界面
- ◆ 内建 RAM 256 Bytes
- ◆ 内建 Flash 8KB
- ◆ 内建 12 MHz 振荡器
- ◆ 3/5V I/O 内建提升电阻
- ◆ 工作温度: 0~70°C
- ◆ 供应电压 : 4.5~5.5V
- ◆ 封装: SOIC-16 pin

3. 脚位圖




图 3-1 : 脚位图

4. 脚位定义

Pin No.	脚位名称	说明	Pin state	Reset State
4	DAT	PS2 Device Interface data	Open drain	HiZ / HiZ
5	CLK	PS2 Device Interface clock	Open drain	HiZ / HiZ
8	D+	USB I/F D+	USB PHY	HiZ / HiZ
9	D-	USB I/F D-	USB PHY	HiZ / HiZ
10	VSS	Power Ground	Power	
11	VCC	Power VCC	Power	
others	P[16:1]	Test Pins	Input pull up	HiZ / HiZ

5. 内部方块图




图 5-1 : 内部方块图

6. 封装(SOIC-16Pin)




图 6-1 : 16-Lead (150-Mil) SOIC

7. 电气特性

7-1 最大极限

Storage Temperature	-65°C to +150°C
Ambient Temperature with Power Applied	-0°C to +70°C
Supply Voltage on VCC Relative to VSS.....	-0.5V to +7.0V
DC Input Voltage	-0.5V to + VCC + 0.5V
DC Voltage Applied to Outputs in High-Z State	-0.5V to + VCC + 0.5V
Power Dissipation	300 mW
Static Discharge Voltage	2200V
Latch-up Current	200 mA

7-2 DC 特性

Parameter	Description	Conditions	Min	Typ.	Max.	Unit
	General					
V _{CC1}	Operating Voltage	No USB activity, 12 MHz	4.2		5.5	V
V _{CC2}	Operating Voltage	USB activity, 12 MHz	4.35		5.25	V
T _{FP}	Operating Temp	Flash Programming	0		70	°C
I _{CC1}	VCC Operating Supply Current	VCC = 5.25V, no loading, 12 MHz			30	mA
I _{CC2}	VCC Operating Supply Current	VCC = 5.0V, no loading, 12 MHz		15		mA
I _{SB1}	Standby Current	Internal Oscillators, Bandgap, Flash, CPU Clock, Timer Clock, USB Clock all disabled			10	µA
USB Interface						
V _{ON}	Static Output High	15K ± 5% Ohm to VSS	2.8		3.6	V
V _{OFF}	Static Output Low	RUP is enabled			0.3	V
V _{DI}	Differential Input Sensitivity		0.2			V
V _{CM}	Differential Input Common Mode Range		0.8		2.5	V
V _{SE}	Single Ended Receiver Threshold		0.8		2	V
C _{IN}	Transceiver Capacitance				20	pF
I _{IO}	Hi-Z State Data Line Leakage	0V < VIN < 3.3V	-10		10	mA

(Continued)

Parameter	Description	Conditions	Min	Typ.	Max.	Unit
	General					
PS2 Device Interface						
R_{UP}	Pull up Resistance		4		12	K Ω
V_{ICR}	Input Threshold Voltage Low, CMOS mode	Low to High edge	40%		65%	VCC
V_{ICF}	Input Threshold Voltage Low, CMOS mode	High to Low edge	30%		55%	VCC
V_{ILTTL}	Input Low Voltage, TTL Mode	I/O-pin Supply = 2.9–3.6V			0.8	V
$V_{IH TTL}$	Input High Voltage, TTL Mode	I/O-pin Supply = 4.0–5.5V	2			V
V_{OL}	Output Low Voltage	IOL2 = 8 mA			0.4	V
V_{OH}	Output High Voltage	IOH = 2 mA	VCC – 0.5			V
C_{LOAD}	Maximum load capacitance				50	pF

7-3 AC 特性

Parameter	Description	Conditions	Min	Typ.	Max.	Unit
USB Driver						
T_{R1}	Transition Rise Time	CLOAD = 200 pF	75			ns
T_{R2}	Transition Rise Time	CLOAD = 600 pF			300	ns
T_{F1}	Transition Fall Time	CLOAD = 200 pF	75			ns
T_{F2}	Transition Fall Time	CLOAD = 600 pF			300	ns
T_R	Rise/Fall Time Matching		80		125	%
V_{CRS}	Output Signal Crossover Voltage		1.3		2.0	V
USB Data Timing						
T_{DRATE}	Low-speed Data Rate	Ave. Bit Rate (1.5 Mbps \pm 1.5%)	1.47 75		1.52 25	Mbps
T_{DJR1}	Receiver Data Jitter Tolerance	To next transition	-75		75	ns
T_{DJR2}	Receiver Data Jitter Tolerance	To pair transition	-45		45	ns
T_{DEOP}	Differential to EOP Transition Skew		-40		100	ns
T_{EOPR1}	EOP Width at Receiver	Rejects as EOP			330	ns

(Continued)

Parameter	Description	Conditions	Min	Typ.	Max.	Unit
USB Data Timing						
T_{EOPR2}	EOP Width at Receiver	Accept as EOP	675			ns
T_{EOPT}	Source EOP Width		1.25		1.5	μ s
T_{EOPT}	Source EOP Width		1.25		1.5	μ s
T_{UDJ1}	Differential Driver Jitter	To next transition	-95		95	ns
T_{UDJ2}	Differential Driver Jitter	To pair transition	-95		95	ns
T_{LST}	Width of SE0 during Diff. Transition				210	ns
PS2 Device Interface						
T_{R_CLK} T_{R_DAT}	Output Rise Time	Measured between 10 and 90% V_{dd}/V_{reg} with 50 pF load			50	ns
T_{F_CLK} T_{R_DAT}	Output Fall Time	Measured between 10 and 90% V_{dd}/V_{reg} with 50 pF load			15	ns




图 7-1 : USB Data Signal Timing




图 7-2 : Receiver Jitter Tolerance




图 7-3 : Differential to EOP Transition Skew and EOP Width




图 7-4 : Differential Data Jitter

8. 应用电路




图 8-1 : 应用电路




图 8-2 : 应用领域